





The Hakki Pilke 43 Pro is an entirely unique firewood processor based on the Easy 42 model, highly regarded among professional users. Despite the increased robustness of the frame, the machine is compact in terms of its dimensions and weight. The productivity of the machine has been improved with the excellent delay-free HakkiSplit™ splitting mechanism as well as new features that ensure uninterrupted material flow - a hydraulic log clamp, a hydraulically retracted measuring device and log landing plates. If the machine is mainly used to process large logs or produce sizeable firewood, buyers can also opt for the wider outfeed conveyor used in the 50 Pro model.

In terms of the operator, the most significant update is the user interface that provides a fully revamped user experience. The HakkiCut™ cutting control always adds optimal cutting force and enables whole cutting operation with one joystick button. Combined with the automatic, hydraulically operated chain tensioner and the automatic chain lubrication pump, which is activated during sawing, these features ensure that the saw chain and bar last for a long time and provide unparalleled sawing efficiency time and time again. When being used the infeeding assistant feeds in a new log automatically during the splitting motion, ensuring that the next log is ready for cutting already during the splitter's return motion.

The 43 Pro model boasts a wealth of features that reduce operating costs. The large oil capacity enables longer oil change intervals and uninterrupted operation in all conditions from Alaska to Australia. Reliable electric control minimizes the number of elements and components that require maintenance. Adjusting the amount of chain oil is easy and replacing the chain oil canister takes only seconds. The power transmission features no v-belts, which ensures consistent reliability and performance year after year with minimal electric or fuel costs.

43 PRO 430/17 MM/IN 600/24 MM/IN 15

- NEW USER INTERFACE
- CONTROLLED LOG LANDING
- HYDRAULIC CHAIN **TENSIONER AS STANDARD**





The log landing plates ensure that even the shortest cut logs land neatly into the splitting groove.



An unparalleled user interface which enables you to process firewood with just two buttons.



The machine's functions can be easily controlled with the ergonomic and easyto-use control panel.



The hydraulic log clamp enables logs of all sizes to be sawed effortlessly.



The AC 10 automatic chain tensioner maintains optimal saw chain tension at all times. The chain can be conveniently replaced after releasing chain tension with the lever pictured - no tools required!

iviax iog ierigtri	000 11111	24
Maximum splitting power	15 t	
Bar	18"	
Power source	PTO, electric	, combi
Splitting blade	6-way	
Outfeed conveyor dimensions	0.25 x 4 m	10"x 13'1"
Infeed conveyor length *	2.5 m	8'2"
CTANIDADD FOLUDMENT		

TECHNICAL SPECIFICATIONS

430 mm

Max log diameter

Splitting blade

Oil heater

HakkiFeed

Powerpack

Large outfeed conveyor with

Outfeed conveyor extension

Blower saw-dust removal

ACCESSORIES

Hakki Pilke Cleaner

Hakki Pilke Roller

hydraulic horizontal and vertical

adjustment (+250 kg / +550 lbs)

Power source	PTO, electric	PTO, electric, combi	
Splitting blade	6-way		
Outfeed conveyor dimensions	0.25 x 4 m	10"x 13'1'	
Infeed conveyor length *	2.5 m	8'2"	
STANDARD EQUIPMENT			
Infeed serial connection kit			
Additional hydraulic infeed roller			
Accessory valve			
Hydraulic infeed conveyor			
Infeed guide plate			
Infeed assist valve			
Hydraulic log clamp			
Safety cover			
AC10 automatic chain tensioner (h	ydraulic)		
HakkiCut™ cutting control			
Automatically optimised cutting sp	eed		
Automatic chain oil lubrication			
Hydraulically retracting log measuri	ing device		
$HakkiSplit^TM$ delay-free splitting (3 s	speeds)		
Guide plates for controlled log land	ding (landing pla	ites)	
Hydraulic height adjustment of the	splitting blade		
Cleaning outfeed conveyor			
Pivoting outfeed conveyor			
Outfeed conveyor speed control +	reverse		
Oil cooler			
Tool box			
DIMENSIONS IN TRANSPO	RT POSITION	\ **	
Height	2,560 mm	8′5″	
Length	2,540 mm	8'4"	
Width	1,400 mm	4'7"	
Weight	1,400 kg	3,087 lbs	
OPTIONAL EQUIPMENT			
Adjustable work platform			

2/4, 8, 12-way

4 m x 400 mm

422, 471, 472

13'1" x 1'4"

16-way for soft wood

3'3"

- GUIDE PLATES FOR
- AUTOMATIC
- POWER WITHOUT COMPROMISING **SPEED**

^{*} length with a hydraulic infeed roller

^{**} combi model with standard conveyor